

## Frequently Asked Questions

Question: Is there any limitation to where DryTronic® can be used?

Answer: Not really, just openly running water, i.e. through a large open hole.

Question: Is it possible for DryTronic® to block leaks through voids, cracks and gaps?

Answer: Yes, it can also improve other things and the overall moisture situation a lot.

Question: On what kind of material could one use DryTronic®?

Answer: Practically any. If you are unsure, please contact your vendor.

Question: Is the DryTronic® system compatible with concrete block basements?

Answer: Yes, it is.

Question: Do we need multiple Drytronic unit types for one building and on multiple walls and floors?

Answer: No, just one individual type is fine.

Question: How many electrodes do we need?

Answer: This depends on the cause and intensity of the humidity. Please complete the diagnostic check-list.

Question: Can a do-it yourself person install the DryTronic® system?

Answer: Yes, many people have done so. If you have any doubts, please ask your vendor.

Question: Are there any systems comparable to DryTronic®?

Answer: No.

Question: Where can I get the latest information about DryTronic®?

Answer: Through your vendor or the Internet at <http://www.drytronic.com>

Question: Where can I send my feedback or questions?

Answer: Preferably to both your vendor **and** to Global Assistance.

If you have any other questions please contact your local authorized vendors' service office.